DC Current (Cur) (Direct Connect CT) 0 - 100mA (Measurement Error Max 0.5%) Smart Box

Product Codes: CuDiSB1138

The DC Current Smart Box is designed for the measuring of DC current from 0 to 100 mA.



Sensor Specifications	
Measurement Type	Via Direct Connect CT
Operating Temperature	0 to 50°C
Storage Temperature	0 to 50°C
Measurement Range	0 to 100 mA
Response Time, (Sensitivity)	15 ms
Repeatability	N/A
Accuracy	0.50%
Life Expectancy	N/A
Sensor Type	Direct Connect CT
Sensor Cable Length	1m
Certified	No

Smart Box Specifications	
Operating Temperature	-40˚C to +85˚C
Storage Temperature	-40 to 105°C
Air Data Rate	250 kb per second
Channels	16 (IEE 802.15.4 channels 11-26)
Hardware Supported Encryption	AES128
Analogue Digital Resolution	Up to 12 bits
Sample time for 12 bit conversion	680µs

BRITISHRESEARCH.COM

British Research Unit 4,
Vale Enterprise Centre, Hayes Rd.,
Sully, Vale of Glamorgan, CF64 5SY UK
Tel. 0044 (0) 1446 734012
Fax. 0044 (0) 5601 258134
Web: www.britishresearch.com

Antenna Options (Range)		Code
Internal	(60m)	i
Large	(700m)	L
Right-Angle	(300m)	R
Small Stub	(300m)	S

Power Supply Option
Standard PSU mains
Water Resistant PSU mains
Battery 9V (Replaceable)
Battery (Rechargeable)
Solar & Battery (Rechargeable)

Smart Box Housing	IP Rating
Indoor	IP50
Outdoor Splash proof	IP51
Outdoor - water jet	IP65
Outdoor - Immersion	Contact Us
Outdoor Explosion Proof	Contact Us